



Meets F.E.M. 1.001

The overall design is made taking advantage of the ELD standard components achieving optimum results in terms of cost-control and delivery time.

Size	Point Hook DIN15401	Code	Rope mm	Load capacities t		Dimensions				Weight kg
				M5	M6	Ø4 mm	A mm	B mm	C mm	
02	1-V	1UB 022 02	7	1,6	1,25	35	152	175	305	11,30
			8							
03	1-V	1UB 032 03	8	2	1,6	35	172	200	317	15,00
			9							
04	1,6-V	1UB 042 04	9	2,5	2	38	180	210	348	18,00
			10							
05	1,6-V	1UB 052 05	10	3,2	2,5	38	200	235	359	22,50
			11							
06	2,5-T	1UB 062 06	11	4 (5)	3,2 (4)	43	228	270	424	43,00
			12							
07	2,5-T	1UB 072 07	12	5	4	43	257	297	424	46,00
			13							
08	4-T	1UB 082 08	13	6,3 (8)	5 (6,3)	48	280	330	491	67,00
			14							
09	4-T	1UB 092 09	15	8	6,3	48	320	375	491	76,00
			16							
10	5-T	1UB 102 10	17	10	8	71	355	425	557	113
			18							
11	5-V	1UB 112 11	19	12,5	10	71	400	470	580	140
			20							